

P14Si QUARTZ PERMANENT GT

Safety Data Sheet

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** P14Si QUARTZ PERMANENT GT
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Product designed for lustering and strengthening car body.
- 1.3 Details of the supplier of the safety data sheet:**
- TENZI Sp. z o.o.
Skarbimierzyce 20
72-002 Dołuje
tel. +48 91 3119777
fax. +48 91 3119779
E-mail address for a competent person responsible for SDS: technolog@tenzi.pl
- 1.4 Emergency telephone number:**
+48 91 31 19 777 (mon. - fri. 8am - 4pm) or 112.

SECTION 2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture:

Classification according to Regulation (EC) No. 1272/2008:
Eye Irrit. 2 H319 – Causes serious eye irritation.

2.2. Label elements:
(According to 1272/2008/EC*)

Hazard symbols:



Signal words:
WARNING

Hazard statements:
H319 – Causes serious eye irritation.

Precautionary statements:
P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards:

Substance does not meet criteria for PBT or vPvB in accordance with Annex XIII of REACH Regulation.

P14Si QUARTZ PERMANENT GT

Safety Data Sheet

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

3.1. Substances:
Not applicable.

3.2. Mixtures:
Composition (according to: 648/2004/EC):

- < 5% cationic surfactants
- < 5% non-ionic surfactants
- organic solvents
- auxiliary substances are not classified as dangerous

Identification	Hazardous ingredient/classification	Concentration
CAS: Not applicable WE: 939-685-4 Index: Not applicable Registration: 01-2119983493-26-XXXX	Quaternary ester compounds Skin Irrit. 2 H315, Eye Dam 1 H318, Aquatic Chronic 3 H412	< 1.2%
CAS: 67-63-0 WE: 200-661-7 Index: 603-117-00-0 Registration: 01-2119457558-25-XXXX	Isopropanol Eye Irrit. 2 H319, Flam Liq. 2. H225, STOT SE 3 H336	< 1%
CAS: Not applicable WE: 919-857-5 Index: Not applicable Registration: 01-2119463258-33-XXXX	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclical, <2% aroma Flam Liq. 3. H226, Asp. Tox. 1 H304, STOT SE 3 H336	< 0.5%

The full texts of H symbols and phrases are in section 16.

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures:

Inhalation:

In case of inhalation poisoning symptoms (cough, dyspnea, dizziness) move the injured to fresh air. Lay him down in semi-recumbent posture and get medical attention.

Skin contact:

If product comes in contact with the skin, immediately remove all contaminated clothing and flush exposed area with large amounts of water. In case of skin changes or burns, get medical attention.

Eye contact:

Flush eyes with running water (at least 15 minutes) while keeping eyelids open. Get medical attention.

Ingestion:

DO NOT induce vomiting. Give lots of water to drink. DO NOT give any neutralizing agents. Immediately get medical attention and show this SDS or label.

4.2. Most important symptoms and effects, both acute and delayed:

Inhalation:

No symptoms.

P14Si QUARTZ PERMANENT GT

Safety Data Sheet

Skin:

May cause irritation after long-time exposure.

Eyes:

Irritant.

Ingestion:

May cause irritation of the mucous membrane.

4.3. Indication of any immediate medical attention and special treatment needed:

Get medical attention.

Fresh water and eye-wash preparations must be available on the worksite.

SECTION 5. FIREFIGHTING MEASURES

5.1. Extinguishing media:**Suitable extinguishing media:**

Use extinguishing measures that are appropriate to local circumstances and surrounding environment.

Unsuitable extinguishing media:

There are not any known extinguishing media that you shouldn't use.

5.2. Special hazards arising from the substance or mixture:

Product is non-flammable.

5.3. Advice for firefighters:

Firefighters should wear self-contained breathing apparatus and full protective clothing. In case of fire, warn the people nearby and evacuate unprotected and untrained personnel from hazard area. Notify relevant emergency services. If possible, remove the containers away from the influence of fire and high temperature. Water may be used to keep fire-exposed containers cool until fire is out. The after burning residues should be removed

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures:

Protective clothes, self-contained breathing apparatus, protective chemical-proof gloves (0.11 mm thick), safety glasses. Avoid skin and eye contact. Provide proper ventilation.

6.2. Environmental precautions:

Avoid discharge into drains, watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up:

In case of unexpected release of the substance into the environment, inform appropriate services about the emergency and remove any source of ignition. Prevent spills from entering sewers, surface water or groundwater. If it is possible, confine and contain the spill by closing the flow of the liquid, plug the damaged container and put it into leakproof wrapping. For a larger spill, make a dike around the outside edges of the spill and use absorbent materials (sand, sawdust, minced limestone). Store clean-up materials for disposal as hazardous waste. Decontaminate polluted area with water.

6.4. Reference to other sections:

See section 8 and 13.

P14Si QUARTZ PERMANENT GT

Safety Data Sheet

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling:

Be careful when working with this product.
Use personal protection recommended in section 8
Mix only with water. DO NOT mix with any other chemical substances.
People with skin allergy or respiratory system problems should not have contact with this product.
Avoid risk – read this instruction sheet carefully before using the product.
After usage, keep container tightly closed and keep it away from unauthorized people.
Use only adequate ventilation to avoid inhalation poisoning.

7.2. Conditions for safe storage, including any incompatibilities:

Store in a tightly closed, original plastic container. Store this product in a dry environment that will be maintained at 5°C - 35°C temperature with a good ventilation system and an easy washable, nonabsorbable alkaline resistant floor.
DO NOT expose the product to sunlight and keep away from heat, sparks, flame and source of ignition.

7.3. Specific end use(s):

No data available.

SECTION 8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

8.1. Control parameters:

Please check any national occupational exposure limit values in your country.

NDS/NDSCh/NDSP values for individual chemical substances (according to SDS or Chemical Safety Report):

Quaternary ester compounds (data for highly concentrated substance):

NDS, NDSCh, NDSP: not identified.

Isopropanol (data for highly concentrated substance):

NDS: 900 mg/m³
NDSCh: 1200 mg/m³
NDSP: not identified.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclical, <2% aroma (data for highly concentrated substance):

NDS, NDSCh, NDSP: unspecified

DNEL /PNEC values for individual chemical substances (according to SDS or Chemical Safety Report):

Quaternary ester compounds (data for highly concentrated substance):

DNEL:

Group: workers, Exposure time: long-term, Exposure route: dermal, Type of effect: systemic effect,	Value: 52.08 mg/kg
Group: workers, Exposure time: long-term, Exposure route: inhalation, Type of effect: systemic effect,	Value: 36.35 mg/m ³
Group: consumers, Exposure time: long-term, Exposure route: dermal, Type of effect: systemic effect,	Value: 31.25 mg/kg
Group: consumers, Exposure time: long-term, Exposure route: inhalation, Type of effect: systemic effect,	Value: 10.85 mg/m ³
Group: consumers, Exposure time: long-term, Exposure route: ingestion, Type of effect: systemic effect,	Value: 6.25 mg/kg

P14Si QUARTZ PERMANENT GT

Safety Data Sheet

PNEC:

Aqua (fresh water):	0.054 mg/l
Aqua (marine water):	0.005 mg/l
Sediment (fresh water):	5.540 mg/kg
Sediment (marine water):	0.554 mg/kg
Sewage treatment plant:	1 mg/l
Soil:	1.08 mg/kg

Isopropanol (data for highly concentrated substance):**DNEL:**

Group: workers, Exposure time: long-term, Exposure route: dermal,	Value: 888 mg/kg/day
Group: workers, Exposure time: long-term, Exposure route: inhalation,	Value: 500 mg/m ³
Group: consumers, Exposure time: long-term, Exposure route: dermal,	Value: 319 mg/kg/day
Group: consumers, Exposure time: long-term, Exposure route: inhalation,	Value: 89 mg/m ³
Group: consumers, Exposure time: long-term, Exposure route: ingestion,	Value: 26 mg/kg/day

PNEC:

Aqua (fresh water):	140.9 mg/l
Aqua (marine water):	140.9 mg/l
Sediment (fresh water):	552 mg/kg
Sediment (marine water):	552 mg/kg
Soil:	28 mg/kg

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclical, <2% aroma (data for highly concentrated substance):**DNEL:**

Group: workers, Exposure time: chronic, Exposure route: dermal, Type of effect: systemic effect,	Value: 300 mg/kg/day
Group: workers, Exposure time: chronic, Exposure route: inhalation, Type of effect: systemic effect,	Value: 1500 mg/m ³
Group: consumers, Exposure time: chronic, Exposure route: dermal, Type of effect: systemic effect,	Value: 300 mg/kg/day
Group: consumers, Exposure time: chronic, Exposure route: inhalation, Type of effect: systemic effect,	Value: 900 mg/m ³
Group: consumers, Exposure time: chronic, Exposure route: ingestion, Type of effect: systemic effect,	Value: 300 mg/kg/day

NOTE: When the concentration of substance is known, personal protective equipment should be chosen based on substance concentration in a workplace, exposure time and operations performed by the employee. In emergency situations, if substance concentration in the workplace is unknown, personal protection of highest class level should be used.

8.2. Exposure controls:**RESPIRATORY PROTECTION:**

Not needed.

HAND PROTECTION:

In case of people with allergy, it is recommended for them to wear protective gloves.
0.11 mm thick.

EYE/FACE PROTECTION:

Safety glasses.

SKIN PROTECTION:

Not needed.

P14Si QUARTZ PERMANENT GT

Safety Data Sheet

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties:

Appearance:	Milky solution
Odour:	Characteristic for materials used in production
Odour threshold:	No data available
pH:	5 ± 1
Melting point:	No data available
Freezing point:	No data available
Initial boiling point:	No data available
Boiling range:	No data available
Flash point:	No data available
Evaporation rate:	No data available
Flammability (solid, gas):	No data available
Upper flammability limit:	No data available
Lower flammability limit:	No data available
Upper explosive limit:	No data available
Lower explosive limit:	No data available
Vapour pressure:	No data available
Vapour density:	No data available
Relative density:	1000 ± 0.020 g/cm ³

Solubility:

A) Water:	soluble
B) Organic solvent:	No data available

Partition coefficient N-Octan:	No data available
Partition coefficient Water:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
Viscosity:	No data available
Explosive properties:	No data available
Oxidising properties:	No data available

9.2. Other information:

Refractive index: Not specified Brix* ± 5%

* - Degrees Brix is the content of an aqueous solution. One degree Brix is 1 gram of sucrose in 100 grams of solution and represents the strength of the solution as percentage by weight (%w/w).

SECTION 10. STABILITY AND REACTIVITY

10.1 Reactivity:

No data available.

10.2 Chemical stability:

Stable under recommended storage conditions (see section 7).

10.3 Possibility of hazardous reactions:

No data available.

10.4 Conditions to avoid:

Avoid heavily warmed rooms without ventilation and long-term exposure to sunlight.

P14Si QUARTZ PERMANENT GT

Safety Data Sheet

10.5 Incompatible materials:

Alkali, chlorine preparations.

10.6 Hazardous decomposition products:

No data available.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

ACUTE TOXICITY:

Inhalation: not applicable.

Skin contact: may cause irritation after long-time exposure.

Eye contact: irritant.

Digestive system: may cause irritation of the mucous membrane after swallowing.

ATEmix = 125 000 (acute toxicity, orally)

DETAILS OF PARTICULAR COMPONENTS (according to substances SDS):

Quaternary ester compounds (data for highly concentrated substance):

LD50: >2000 mg/kg (mouse, orally) (OECD 423)

LD50: >2000 mg/kg (rabbit, dermal) (OECD 402)

Skin irritation (rabbit) (OECD 404)

Serious eye irritation (rabbit) (OECD 405)

No allergic effect (guinea pig) (Magnusson - Kligman test)

Teratogenicity:

NOAEL: 1000 mg/kg (rat, orally) (OECD 414)

Developmental toxicity:

NOAEL: 1000 mg/kg (rat, orally)

Reproductive toxicity:

NOAEL: 1000 mg/kg (rat, orally)

Isopropanol (data for highly concentrated substance):

Data for 100% concentrated isopropanol:

LD50: > 2000 mg/kg (orally)

LD50: > 2000-13500 mg/kg (dermal)

LC50: > 5 mg/l (inhalation)

Slight eye irritation detected.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclical, <2% aroma (data for highly concentrated substance):

LD50: >5000 mg/kg (rat, orally) (OECD 401)

P14Si QUARTZ PERMANENT GT

Safety Data Sheet

LD50: >5000 mg/kg (rat, dermal) (OECD 402)
LC50: >4951 mg/m³/4h (rat, inhalation) (OECD 403)

Skin and eye irritation detected.
Substance is toxic to organs or biological system.
One-time exposure may induce drowsiness and dizziness.
Vapour concentration above recommended exposure levels result in irritating eyes and respiratory system.
Aspiration danger when swallowed.

SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity:

Data for the mixture ingredients:

Quaternary ester compounds (data for highly concentrated substance):

LC50: > 10 mg/l/96h (fish, half-static) (OECD 203)
EC50: > 8.6 mg/l/48h (invertebrates, half-static) (OECD 202)
NOEC: 0.39 mg/l/72h (algae, static) (OECD 201)
EC50: 1.2 mg/l/72h (algae, static) (OECD 201)
EC50: 10 mg/l/6 days (microorganisms) (active sediment)
EC50: 100 mg/l/6 days (microorganisms) (active sediment)

Isopropanol (data for highly concentrated substance):

LC50: >100 mg/l/48h (fish, *Leuciscus idus melanotus*)
EC50: >100 mg/l/48h (daphnia, *Daphnia magna*)
EC50: >100 mg/l/72h (algae, *Scendesmus subspicatus*)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclical, <2% aroma (data for highly concentrated substance):

EL0: 1000 mg/l/48h (daphnia, *Daphnia magna*)
NOERL: 100 mg/l/72h (algae)
EL50: 1000 mg/l/72h (*Pseudokirchneriella subcapitata*)
LL50: >1000 mg/l/96h (fish, *Oncorhynchus mykiss*)

12.2. Persistence and degradability:

The surfactants contained within the product comply with the biodegradability criteria as laid down in Regulation (EC) No 648/2004 on detergents.

Data for the mixture ingredients:

Substance	Method	Length	Degraded percentage
Quaternary ester compounds	No data available	No data available	> 60%
Isopropanol	No data available	10 days	> 70%
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclical, <2% aroma	Easily degradable	Easily degradable	Easily degradable

P14Si QUARTZ PERMANENT GT

Safety Data Sheet

12.3. Bioaccumulative potential:

Bioaccumulation is incredible.
Data based on mixture ingredients.

12.4. Mobility in soil

The product is water soluble and may sink into groundwater systems.

12.5. Results of PBT and vPvB assessment:

This substance/mixture does not meet the PBT and vPvB criteria of REACH, annex XIII..

12.6. Other adverse effects:

No data available.

SECTION 13. DISPOSAL CONSIDERATIONS

RESIDUES AND WASTES:

DO NOT mix with other liquid wastes.

DO NOT empty into sewage system. Product should be totally used up according to its description.

If it's impossible to do so, dispose of this material and its container at hazardous or special waste collection point.

13.1. Waste treatment methods:

Contaminated containers should be completely emptied. Several times rinse the container promptly after emptying. Empty container can be stored in containers for collection of plastic packaging, or can be delivered to specialized company for recycling.

Disposal should be in accordance with the national/international regulations.

SECTION 14. TRANSPORT INFORMATION

TRADE NAME: P14Si QUARTZ PERMANENT GT

- 14.1. UN Number: Not applicable.
14.2. UN proper shipping name: Not applicable.
14.3. Transport hazard class(es): Not applicable.
14.4. Packing group: Not applicable.
14.5. Environmental hazards: No.
14.6. Special precautions for user: For more details see Sections 6 and 8.
14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: No data available.

WARNING LABELS

not applicable

P14Si QUARTZ PERMANENT GT

Safety Data Sheet

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture:

- 1) COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).
- 2) REGULATION (EC) No 648/2004 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 31 March 2004 on detergents.
- 3) COMMISSION REGULATION (EC) No 907/2006 of 20 June 2006 amending Regulation (EC) No 648/2004 of the European Parliament and of the Council on detergents, in order to adapt Annexes III and VII thereto.
- 4) REGULATION (EC) No 1336/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 amending Regulation (EC) No 648/2004 in order to adapt it to Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.
- 5) COMMISSION REGULATION (EC) No 551/2009 of 25 June 2009 amending Regulation (EC) No 648/2004 of the European Parliament and of the Council on detergents, in order to adapt Annexes V and VI thereto (surfactant derogation).
- 6) REGULATION (EU) No 259/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 14 March 2012 amending Regulation (EC) No 648/2004 as regards the use of phosphates and other phosphorus compounds in consumer laundry detergents and consumer automatic dishwasher detergents.
- 7) REGULATION (EC) No 273/2004 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 11 February 2004 on drug precursors).
- 8) REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

15.2. Chemical safety assessment

For mixture:

A Chemical Safety Assessment has not been carried out.

For following mixture substances:

Quaternary ester compounds:

A Chemical Safety Assessment has been carried out.

Isopropanol:

A Chemical Safety Assessment has been carried out.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclical, <2% aroma:

A Chemical Safety Assessment has been carried out.

SECTION 16. OTHER INFORMATION

Information above is based on current knowledge of product in its current form.

All data are presented in order to take into account safety requirements priority and not to guarantee special properties of the product. If product usage conditions are not under manufacturer control, responsibility for safe use lies with the person that uses them. The employer is obliged to inform all employees, who have contact with the product, about the risk and safety measures specified in the data sheet. Safety data presented above were prepared based on safety characteristics of substances used by the producer to compose the product and based on regulations for handling dangerous substances and their preparation. Classification of chemical mixture was done with calculation methods, based on the content of hazardous ingredients.

The full list of symbols and H phrases from Section 2 and 3:

- Aquatic Chronic 3** – Hazardous to the aquatic environment - Chronic Hazard, category 3.
Eye Dam. 1 – Serious eye damage, category 1.
Skin Irrit. 2 – Causes skin irritation, category 2.
Eye Irrit. 2 – Causes serious eye irritation, category 2.
STOT SE 3 – Specific target organ toxicity - Single exposure STOT, category 3.
Flam Liq. 2 – Flammable liquid and vapour, category 2.
Flam Liq. 3 – Flammable liquid and vapour, category 3.
Asp. Tox. 1 – May be fatal if swallowed and enters airways.

P14Si QUARTZ PERMANENT GT

Safety Data Sheet

H225	– Highly flammable liquid and vapour.
H226	– Flammable liquid and vapour.
H304	– May be fatal if swallowed and enters airways.
H315	– Causes skin irritation.
H318	– Causes serious eye damage.
H319	– Causes serious eye irritation.
H336	– May cause drowsiness or dizziness.
H412	– Harmful to aquatic life with long lasting effects.

More information on the product can be found on the specific technical data sheet which is available on www.tenzi.pl

Training:

Course participants should be trained about how to handle this hazardous substance, about safety and work hygiene. Drivers should also be trained and obtain proper certification in accordance with the ADR requirements.

Expiry date:

36 months from the production date (if product is stored according to the producent recommendations)

Changes compared to the previous version:

- section 9 (pH value).

Updated cards versions are now available on www.tenzi.pl

This Safety Data Sheet contains 11 pages. Changes in the content by unauthorized people is prohibited.